

Technical Sheet

- Mechanic actuation
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- Other versions compliant with: NF Standard
- EN 14055 marking CL1
- Supplied with anti-condensation lining

Structure

- Metal, corrosion resistant
- Metallic links
- Optional corner kit
- Height regulation of the adjustable (0-200 mm);
- 300mm, reduced width
- Depth adjustable outlet bend
- Tested for 400kg load

Accessories

- 1 Discharge pipe \varnothing 90 x 315
- 1 Seal for discharge pipe \varnothing 125
- 1 Connecting pipe \varnothing 45 x 180
- 1 Pan rubber seal \varnothing 45
- 1 Protective box
- 1 G 1/2" stop valve
- 1 Protection sponge for the stop valve
- 1 Flush bend \varnothing 90 / 90 L230
- 1 Protection pipe \varnothing 90
- 1 Protection pipe \varnothing 45
- 1 Adaptor pipe \varnothing 90/110

For fixing wall structure:

- 4 Galvanized screws M8x60
- 4 Galvanized washers M8 DIN 9021
- 4 Bushing for metal structure
- 2 Fixing Metallic links

Fixing accessories for toilet bowl mounting on the structure:

- 2 Threaded rods M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Washers for WC pan fixation
- 2 Nuts M12
- 2 Washers \varnothing 34

Warranty

- Ten (10) years warranty against manufacturing defects according to the general selling terms. Starting from the purchase date of the product (excludes perishable parts).
- If the product is not correctly installed the warranty is not valid